



كثلة كجم	(الحد من السرعة (دورة في الدقيقة (تقييمات الحمل الأساسية (كيلو نيوتن	(الأبعاد الحدودية (مم	تحمل رقم						
زيت	(ثابت) (كور	(ديناميكي) (كور	ج	د:	د:	مهاجم	د:		
21500	11300	12400	16	25	14	8	NKI8	46	
21700	7002	6200	12	19	12	9	NKI9/12	14.6	
19650	10500	9808	16	22	14	10	NKI10/16	27.3	
21000	18400	14000	20	24	16	12	NKI12/20	39	
19100	12853	8847	16	27	19	15	NKI15/16	38	
19100	19053	12347	20	27	19	15	NKI15/20	45.7	
20000	18200	13000	16	29	21	17	NKI17/16	41.4	
16700	17000	10800	16	32	24	20	NKI20/16	48.5	
16200	15340	8721	16	34	25	22	NKI22/16	50	
14000	56000	31500	30	38	29	25	NKI25/30	115	
11134	51350	22200	30	50	40	35	NKI35/30	165	
10127	48000	22000	20	55	45	40	NKI40/20	124	
10127	86000	35000	30	55	45	40	NKI40/30	184	
9500	52500	26000	20	57	47	42	NKI42/20	138	
8567	70000	36000	25	62	50	45	NKI45/25	218	
8567	102000	41500	35	62	50	45	NKI45/35	289	
7890	78000	32000	25	68	55	50	NKI50/25	262	
7256	126800	48000	35	72	60	55	NKI55/35	357	
7156	85000	35500	25	82	68	60	NKI60/25	388	